

缓冲用U形圈 H1



装配例			型式例																																																																																																														
			截面图	材料	温度范围	压力	速度	特点	代号																																																																																																								
				PU + PA	-40至100	≤50	≤0.5	封隔高温介质，吸收高负荷冲击压力，保护主密封	H1																																																																																																								
			<table border="1"> <thead> <tr> <th>d</th><th>D</th><th>L</th> <th>d</th><th>D</th><th>L</th> <th>d</th><th>D</th><th>L</th> <th>d</th><th>D</th><th>L</th> <th>d</th><th>D</th><th>L</th> </tr> </thead> <tbody> <tr> <td>35.5</td><td>51</td><td>6.3</td> <td>65</td><td>80.5</td><td>6.3</td> <td>95</td><td>110.5</td><td>6.3</td> <td>125</td><td>140.5</td><td>6.3</td> <td>160</td><td>175.5</td><td>6.3</td> </tr> <tr> <td>40</td><td>55.5</td><td>6.3</td> <td>70</td><td>85.5</td><td>6.3</td> <td>100</td><td>115.5</td><td>6.3</td> <td>130</td><td>145.5</td><td>6.3</td> <td>170</td><td>185.5</td><td>6.3</td> </tr> <tr> <td>45</td><td>60.5</td><td>6.3</td> <td>75</td><td>90.5</td><td>6.3</td> <td>105</td><td>120.5</td><td>6.3</td> <td>132</td><td>147.5</td><td>6.3</td> <td>180</td><td>195.5</td><td>6.3</td> </tr> <tr> <td>50</td><td>65.5</td><td>6.3</td> <td>80</td><td>95.5</td><td>6.3</td> <td>110</td><td>125.5</td><td>6.3</td> <td>135</td><td>150.5</td><td>6.3</td> <td>190</td><td>205.5</td><td>6.3</td> </tr> <tr> <td>55</td><td>70.5</td><td>6.3</td> <td>85</td><td>100.5</td><td>6.3</td> <td>115</td><td>130.5</td><td>6.3</td> <td>140</td><td>155.5</td><td>6.3</td> <td>200</td><td>221</td><td>8</td> </tr> <tr> <td>60</td><td>75.5</td><td>6.3</td> <td>90</td><td>105.5</td><td>6.3</td> <td>120</td><td>135.5</td><td>6.3</td> <td>150</td><td>165.5</td><td>6.3</td> <td>210</td><td>231</td><td>8</td> </tr> </tbody> </table>									d	D	L	d	D	L	d	D	L	d	D	L	d	D	L	35.5	51	6.3	65	80.5	6.3	95	110.5	6.3	125	140.5	6.3	160	175.5	6.3	40	55.5	6.3	70	85.5	6.3	100	115.5	6.3	130	145.5	6.3	170	185.5	6.3	45	60.5	6.3	75	90.5	6.3	105	120.5	6.3	132	147.5	6.3	180	195.5	6.3	50	65.5	6.3	80	95.5	6.3	110	125.5	6.3	135	150.5	6.3	190	205.5	6.3	55	70.5	6.3	85	100.5	6.3	115	130.5	6.3	140	155.5	6.3	200	221	8	60	75.5	6.3	90	105.5	6.3	120	135.5	6.3	150	165.5	6.3
d	D	L	d	D	L	d	D	L	d	D	L	d	D	L																																																																																																			
35.5	51	6.3	65	80.5	6.3	95	110.5	6.3	125	140.5	6.3	160	175.5	6.3																																																																																																			
40	55.5	6.3	70	85.5	6.3	100	115.5	6.3	130	145.5	6.3	170	185.5	6.3																																																																																																			
45	60.5	6.3	75	90.5	6.3	105	120.5	6.3	132	147.5	6.3	180	195.5	6.3																																																																																																			
50	65.5	6.3	80	95.5	6.3	110	125.5	6.3	135	150.5	6.3	190	205.5	6.3																																																																																																			
55	70.5	6.3	85	100.5	6.3	115	130.5	6.3	140	155.5	6.3	200	221	8																																																																																																			
60	75.5	6.3	90	105.5	6.3	120	135.5	6.3	150	165.5	6.3	210	231	8																																																																																																			